



The new generation of skid steer loaders.







Powered with technology.

Elise 900. The world's first electric skid steer loader represents the highest technology and years of experience of FIRSTGREEN Industries.

Battery endurance

4+ hours

Dependant on use, conditions and configuration

Hinge pin height

3665

384 mm higher reach than the competing average

Battery capacity

240 Ah

With hot-swap battery capability

100% electric, extremely low noise, 0 emission

On stock in 3 days

Low operational costs
Retrofitable modular construction
Microspeed for precise control
Self-leveling gyro platform

Chassis clearance

262 mm

44 mm higher than competing average

Remote control

50_m

15 m with smart app

Loading capacity

900 kg

Suitable for most construction tasks

Technical specs.



| GENERAL SPECIFICATIONS | |
|------------------------|-----------|
| Rated load capacity | 900 kg |
| Tipping load | 1 800 kg |
| Minimum travel speed | 0.15 km/h |
| Maximum speed | 12 km/h |
| Maximum travel speed | 12 km/h |

| MOTOR | |
|----------------------|---------------|
| Electric engine type | 3x Best Motor |
| Rated power | 3x10 kW |
| Maximum power | 3x27 kW |
| Maximum torque | 3x160 Nm |

TUNE-UP YOUR MACHINE

Options

- Air conditioning
- Windowless cabin re-build set
- · Hard-mounted display
- · Rubber or steel track set for increased traction
- · Cable set pre-install for electric attachments
- Danfoss remote control
- · Lifting points
- Set of wheel with universal tires, heavy terrain tires, smooth surface tires or solid tires
- Set of marking and accessories for road operation


Standard features

- Lead-acid battery with capacity 240 Ah
- External battery charger
- · Electric heater
- Battery cover opening for quick battery change
- GPS module
- Apple/Android smartphone with control app
- Rear-view camera
- Left and right rear view mirrors
- · Mandatory lightning
- Front work light

- Rear work lights
- Orange beacon light
- Travel alarm
- Emergency exit window
- Front roller sunshade
- Roof tinted glass
- Windscreen wiper with washer
- Safety reinforced cab
- Seat, door and seatbelt sensors
- Speed coupler SAE J2513
- Self leveling bucket system
- Multiple control option ISO, H pattern and inverted H pattern

Compare technical specifications for this product online at first.green

ELISE 900



| 225 | מולודינינו מולודינינינו מולודינינו מולודינינינו מולודינינינינינינינינינינינינינינינינינינינ |
|------|--|
| 7007 | 1880 and 188 |

| WEIGHTS | |
|----------------------------|----------|
| Rated operating weight | 3 300 kg |
| Total weight of the loader | 4 200 kg |

| HYDRAULICS | |
|-------------------------|----------|
| Hydraulic oil pressure | 180 Bar |
| Hydraulic oil flow | 65 l/min |
| Hydraulic oil reservoir | 40 I |



With a wide range of attachments.



Standard bucket



Concrete mixer



Pallet forks



Hammer



Auger



... plus **34 other** attachments on first.green



For more FIRSTGREEN products, visit **first.green**

+420 737 633 733, info@first.green